

Littleville Fair **DEMOLITION DERBY**

Saturday, August 3, 2024 5:00 pm Start



Get your cars ready for the **2nd Annual Littleville Fair Demolition Derby**

Contact Moe Boisseau 413-364-4411 for more information

For Rules & Information, visit the Littleville Fair website or Facebook page: www.littlevillefair.com | www.facebook.com/Littleville15

Littleville Fairgrounds, 15 Kinnebrook Rd., Chester, MA 01011



Saturday, August 3, 2024, 5pm

4 Cylinder Class Rules

- 1) No reinforcements of any kind except what is within the rules stated here after and is only for 4 cylinder class.
- 4 cylinder compact size stock hardtop automobile or station wagons allowed. You may use foreign cars, and front wheel drive automobiles. **No trucks, jeeps, off road vehicles, rear engine, or mid-engine automobiles allowed.** Maximum wheelbase of 106 inches, minimum wheelbase of 89 inches will be allowed. If your vehicle is all wheel drive, you must disable either the front or rear drivetrain (can only be two wheel drive.) No mini subcompacts, micro vehicles, or amc pacers will be allowed.
- 3) No reinforcements of any kind will be allowed. Only exception will be driver side. Door may not exceed eight inches(8) past the vertical seams of the door. You may insert a dash bar maximum of 2 ½ inches in diameter from A pillar to A pillar if the dash is removed. You may use a seat bar from B pillar to B pillar maximum 2 ½ inches in diameter. Trailer hitches or any other type of stiffening devices are considered reinforcements and must be removed. You may weld rear ends or differentials to create a positive traction rear end. Rear ends can not be chained. No mini truck rear ends. No solid shocks or adding extra clamps or springs to suspension (suspension must work freely.) Maximum bumper height 20 inches from the ground to the center of the bumper. It is a suggestion that you may attach two vertical rods or chains approximately 12 inches from each side of the windshield opening to protect the driver from the hood coming off and collapsing into the driver's compartment.
- 4) All glass must be removed.
- 5) All broken glass must be vacuumed up.

- 6) All interior, except driver's seat and dashboard, must be removed. Bench seats are OK. Relocation of battery to passenger floor is permitted.
- 7) No studded tires will be allowed.
- **8)** All wheel weights must be removed.
- **9)** Helmet, eye protection, long sleeve shirt and pants required.
- **10)** Neck braces are encouraged, but at driver's discretion.



Saturday, August 3, 2024, 5pm

6 Cylinder Class Rules

- 1) No reinforcements of any kind except what is within the rules stated here after and is only for 6 cylinder class.
- 2) 6 cylinder stock hardtop automobiles or station wagons will be allowed. This includes foreign automobiles. You may use front wheel drive vehicles. No trucks, jeeps, hearses, limos, ambulances, convertibles, suvs, rear engine automobiles, 4x4s, Camaros, Firebirds, El Caminos, Chrysler imperials, or imperial subframes. Full size automobiles must have a wheelbase of 105 inches or greater; wheelbase is measured from center of hub to center of hub.
- 3) No reinforcements of any kind will be allowed. Only exception will be the driver side front door and you may insert a dash bar from A pillar to A pillar(a maximum of 2 ½ inches in diameter of all bars if you remove your dash.) You can also install a bar not to exceed 2 ½ inches in diameter from B pillar to B pillar. If you use a seat bar, you must wear a neck brace to prevent whiplash. Trailer hitches or any other type of stiffening devices are considered reinforcements and must be removed. You may weld rear ends or differentials to create a positive traction rear end. Rear ends can not be chained. No truck rear ends. No flipping of the rear ends. No leaf spring conversions, or leaf over conversions will be permitted. No solid shocks or adding extra clamps or springs to suspension (suspension must work freely.) Vehicles must have stock leaf springs and can not have any more than 6 leaves per side. On the older steel bumpers you may weld the outer skin to the bumper with a maximum of four(4), three(3) inch weld on top of the bumper and on the bottom of the bumper (a maximum of eight (8), three (3) inch welds). Maximum bumper height of 20 inches measured from ground to the center of the bumper. No engine cradles of

any kind. No solid welded motor mounts, or transmission mounts. Motor mounts must have a rubber between frame bracket and motor mount. Must run stock type transmission mount bracket. No tilting of frames. No slip drive shafts. It is a suggestion that you may attach two vertical rods of chains approximately 12 inches from each side of the windshield opening to protect the driver from the hood coming off and collapsing into the driver's compartment.

- 4) All glass must be removed.
- 5) All broken glass must be vacuumed up.
- 6) All interior, except driver's seat and dashboard, must be removed. Bench seats are OK. Relocation of battery to passenger floor is permitted.
- 7) No studded tires will be allowed.
- 8) All wheel weights must be removed.
- 9) Helmet, eye protection, long sleeve shirt and pants required.
- **10)** Neck braces are encouraged, but at driver's discretion.



Saturday, August 3, 2024, 5pm

8 Cylinder Class Rules

- 1) No reinforcements of any kind except what is within the rules stated here after and is only for 8 cylinder class.
- 8 cylinder stock hardtop automobiles or station wagons will be allowed. This includes foreign automobiles. You may use front wheel drive vehicles. No trucks, jeeps, hearses, limos, ambulances, convertibles, suvs, rear engine automobiles, 4x4s, Camaros, Firebirds, El Caminos, Chrysler imperials, or imperial subframes. Full size automobiles must have a wheelbase of 105 inches or greater; wheelbase is measured from center of hub to center of hub.
- 3) No reinforcements of any kind will be allowed. Only exception will be the driver side front door and you may insert a dash bar from A pillar to A pillar(a maximum of 2 ½ inches in diameter of all bars if you remove your dash.) You can also install a bar not to exceed 2 ½ inches in diameter from B pillar to B pillar. If you use a seat bar, you must wear a neck brace to prevent whiplash. Trailer hitches or any other type of stiffening devices are considered reinforcements and must be removed. You may weld rear ends or differentials to create a positive traction rear end. Rear ends can not be chained. No truck rear ends. No flipping of the rear ends. No leaf spring conversions, or leaf over conversions will be permitted. No solid shocks or adding extra clamps or springs to suspension (suspension must work freely.) Vehicles must have stock leaf springs and can not have any more than 6 leaves per side. On the older steel bumpers you may weld the outer skin to the bumper with a maximum of four(4), three(3) inch weld on top of the bumper and on the bottom of the bumper (a maximum of eight (8), three (3) inch welds). Maximum bumper height of 24 inches measured from ground to the center of the bumper. No engine cradles of

any kind. No solid welded motor mounts, or transmission mounts. Motor mounts must have a rubber between frame bracket and motor mount. Must run stock type transmission mount bracket. No tilting of frames. No slip drive shafts. It is a suggestion that you may attach two vertical rods of chains approximately 12 inches from each side of the windshield opening to protect the driver from the hood coming off and collapsing into the driver's compartment.

- 4) All glass must be removed.
- 5) All broken glass must be vacuumed up.
- 6) All interior, except driver's seat and dashboard, must be removed. Bench seats are OK. Relocation of battery to passenger floor is permitted.
- 7) No studded tires will be allowed.
- 8) All wheel weights must be removed.
- 9) Helmet, eye protection, long sleeve shirt and pants required.
- **10)** Neck braces are encouraged, but at driver's discretion.



Saturday, August 3, 2024, 5pm

AWD Class Rules

- 1) No reinforcements of any kind except what is within the rules stated here after and is only for 6 cylinder class.
- 2) 6 cylinder stock hardtop automobiles or station wagons will be allowed. This includes foreign automobiles. You may use front wheel drive vehicles. No trucks, jeeps, hearses, limos, ambulances, convertibles, suvs, rear engine automobiles, 4x4s, Camaros, Firebirds, El Caminos, Chrysler imperials, or imperial subframes. Full size automobiles must have a wheelbase of 105 inches or greater; wheelbase is measured from center of hub to center of hub.
- 3) No reinforcements of any kind will be allowed. Only exception will be the driver side front door and you may insert a dash bar from A pillar to A pillar(a maximum of 2 ½ inches in diameter of all bars if you remove your dash.) You can also install a bar not to exceed 2 ½ inches in diameter from B pillar to B pillar. If you use a seat bar, you must wear a neck brace to prevent whiplash. Trailer hitches or any other type of stiffening devices are considered reinforcements and must be removed. You may weld rear ends or differentials to create a positive traction rear end. Rear ends can not be chained. No truck rear ends. No flipping of the rear ends. No leaf spring conversions, or leaf over conversions will be permitted. No solid shocks or adding extra clamps or springs to suspension (suspension must work freely.) Vehicles must have stock leaf springs and can not have any more than 6 leaves per side. On the older steel bumpers you may weld the outer skin to the bumper with a maximum of four(4), three(3) inch weld on top of the bumper and on the bottom of the bumper (a maximum of eight (8), three (3) inch welds). Maximum bumper height of 20 inches measured from ground to the center of the bumper. **No engine cradles of**

any kind. No solid welded motor mounts, or transmission mounts. Motor mounts must have a rubber between frame bracket and motor mount. Must run stock type transmission mount bracket. No tilting of frames. No slip drive shafts. It is a suggestion that you may attach two vertical rods of chains approximately 12 inches from each side of the windshield opening to protect the driver from the hood coming off and collapsing into the driver's compartment.

- 4) All glass must be removed.
- 5) All broken glass must be vacuumed up.
- 6) All interior, except driver's seat and dashboard, must be removed. Bench seats are OK. Relocation of battery to passenger floor is permitted.
- 7) No studded tires will be allowed.
- 8) All wheel weights must be removed.
- 9) Helmet, eye protection, long sleeve shirt and pants required.
- **10)** Neck braces are encouraged, but at driver's discretion.



Saturday, August 3, 2024 5pm

TOTAL CASH PURSE \$1,200

Name:	Age	D.O.B	Car #
Driver's License #		_ Expiration [Date:
Address:			
City:	State:	Zip:	
Email Address:			
I HAVE READ THE RULES AND WI GROUND OR TRACK IN ITS PRESE		JUDGES AS FINAL AI	ND ELECT TO USE THE
Date:	Signature:		
Phone Number:	C	ell:	
Please indicate what type of v \$35.00 per vehicle entered.	vehicle you will be entering (mo	ark all that apply).	Remember the entry fee is
TOTAL # OF VEHICLES ENT	ERED: X \$35.00	=	
No. of Cylinders (mark all th	hat apply): 4 Cyl: 6 C	yl: 8 Cyl:	AWD:
ALSO NOTE: You may choose y	your own numbers but it will b for fair entry at time of sign up		ster basis. Driver and one

www.Littlevillefair.com